

DIGITAL TACHOMETER

MS6208A / MS6208B

MS6208A

RANG
50~19999 RPM

Apo MAX MIN AVG
MEM H ☀
RPM



Specifications		MS6208A	
Specifications	Range	Resolution	Accuracy
Contact Measurement	50~99.99RPM	0.01RPM	±(0.03%+2)
	100~9999.9RPM	0.1RPM	±(0.03%+2)
	10000~19999RPM	1RPM	±(0.03%+2)
Features			
Auto Power Off	Auto Power Off		●
MAX/MIN/AVG			●
Unit selection	m/min m/sec ft/min ft/sec in/min		●
Data Logging	100 groups		●
Data Hold			●
Display Backlight			●
LBD	Low Battery Display		●
General			
Power Supply	4x1.5AAA Batteries		
Product Size	170mmx60mmx27mm/6.7"x2.4"x1.1"		
Product Weight	130g/0.28lb		
Safety Rating	CE RoHS		

MS6208B

RANG
50~99999 RPM

Apo MAX MIN AVG
MEM H ☀
RPM



Specifications		MS6208B	
Specifications	Range	Resolution	Accuracy
Non-Contact Measurement (Photo)	50~99.99RPM	0.01RPM	±(0.03%+2)
	100~9999.9RPM	0.1RPM	±(0.03%+2)
	10000~99999RPM	1RPM	±(0.03%+2)
Features			
Measuring Distance	50mm~250mm		●
Auto Power Off	Auto Power Off		●
MAX/MIN/AVG			●
Unit selection	m/min m/sec ft/min ft/sec in/min		●
Data Logging	100 groups		●
Data Hold			●
Display Backlight			●
LBD	Low Battery Display		●
General			
Power Supply	4x1.5AAA Batteries		
Product Size	155mmx60mmx27mm/6.1"x2.4"x1.1"		
Product Weight	120g/0.26lb		
Safety Rating	CE RoHS		

DIGITAL ANEMOMETER

MS6252A / MS6252B



Specifications		MS6252A MS6252B	
Specifications	Range	Accuracy	
m/s (meter per second)	0.80~30.00 m/s	±(2.0%+50)	±(2.0%+50)
	30.00~40.00 m/s	For Reference only	
km/h (kilometer per hour)	1.40~108.00 km/h	±(2.0%+50)	±(2.0%+50)
	108.00~144.00 km/h	For Reference only	
ft/s (feet per second)	1.30~98.50 ft/s	±(2.0%+50)	±(2.0%+50)
	98.50~131.20 ft/s	For Reference only	
Knots (nautical miles per hour)	0.80~58.30 knots	±(2.0%+50)	±(2.0%+50)
	58.30~77.70 knots	For Reference only	
mile/h (mile per hour)	0.90~67.20 mil/h	±(2.0%+50)	±(2.0%+50)
	67.20~90.00 mil/h	For Reference only	
ft/m (feet per minute)	78~5900 ft/m	±(2.0%+50)	±(2.0%+50)
	5900~7874 ft/m	For Reference only	
Air Volume Unit	CFM	0~9.9990ft ³	
	CMM	0~9.9990m ³	
	CMS	0~9.999m ³	
Temperature	-20~60°C		±1.5°C
	-4~140°F		±2.7°F
Relative Humidity	(20~80%) RH		±3%
	(<20~>80%) RH		±5%
Features			
Display	counts	9999	9999
APO	Auto Power Off	●	●
Flow Area Setting		●	●
MAX/MIN		●	●
°C/°F Selection		●	●
Data Hold		●	●
Ambient			●
Dew Point			●
Wet Bulb			●
Temperature			●
Display Backlight		●	●
LBD	Low Battery Display	●	●
USB Interface	(Windows OS)		●
General			
Power Supply	1×9V 6F22 Battery		
Product Size	165mm×85mm×38mm/6.5"×3.3"×1.5"		
Product Weight	168g/0.37lb		
Safety Rating	CE RoHS		

● Feature Difference



MS6252A

CFM 99990 9.9990ft³
CMM 99990 9.9990m³
CMS 9999 9.999m³
m/s km/h ft/s
knots mile/h ft/m
CFM CMM CMS
Apo MAX MIN H
☀



MS6252B

CFM 99990 9.9990ft³
CMM 99990 9.9990m³
CMS 9999 9.999m³
m/s km/h ft/s
knots mile/h ft/m
CFM CMM CMS
DP WB
°F/°C ☀ USB
Apo MAX MIN H
☀

ติดต่อบริษัท นีโอนิคส์ จำกัด

Tel: 02-077-7602 หรือ 061-8268939

E-mail: sale@neonics.co.th

เว็บไซต์ www.neonics.biz