

Vibration Meter



GM63A



GM63B

Technical indicators	GM63A	GM63B
Measuring range	Acceleration: 0.1~199.9m/s ³ Speed : 0.1~199.9m/s Displacement: 0.001~1.999mm P-P	
Measurement error	±5%±2digits	
Vibration acquisition	Piezoelectric accelerometer (shear)	
Acceleration measurement range	10Hz~1KHz (LO) 1KHz~15KHz (HI)	
Speed frequency measurement range	10Hz~1KHz (LO)	
Displacement frequency measurement range	±10Hz~1KHz (LO)	
Data output	AC output 2 v Peak (showing full range) Load: 10 k Ω or high resistance headset can be connected	
Data replacement cycle	1s	
Working temperature range	0~40℃	
Working humidity range	30~90%RH	
Peculiarity		
Maximum lock	×	√
Unit conversion	×	√
According environment	×	√
AC signal output interface	√	×
Measuring value/status	√	√
Measure the acceleration/velocity/displacement	√	√
A magnetic chuck	×	√
Low electricity prompt	√	√
LCD backlight shows	√	√
Automatic shutdown	√	√
Conventional		
Power supply	9V batteries	9V batteries
Product size	183*67*30mm	150*38*80mm
Product weight	182g(+batteries)	229g(+batteries)
Standard Quantity Per Carton	12PCS	12PCS
Standard Carton Size	51.1*40.5*32cm	51.1*40.5*32cm
Standard Carton gross weight	12.8kg	14.4kg

ติดต่อบริษัท เนโอเนิกส์ จำกัด

Tel: 02-077-7602 หรือ 061-8268939

E-mail: sale@tools.in.th หรือ sale@neonics.co.th