

PM6513/PM6514

Industry Digital Thermometer



SPECIFICATIONS	Range	Resolution	Accuracy
J-type	-200~0°C	0.1°C/°F	±(0.2%+1°C)
	0~1200°C	0.1°C/°F	±(0.2%+0.5°C)
K-type	-200~0°C	0.1°C/°F	±(0.2%+1°C)
	0~1370°C	0.1°C/°F	±(0.2%+0.5°C)
T-type	-200~0°C	0.1°C/°F	±(0.2%+1°C)
	0~400°C	0.1°C/°F	±(0.2%+0.5°C)
E-type	-150~0°C	0.1°C/°F	±(0.2%+1°C)
	0~1000°C	0.1°C/°F	±(0.2%+0.5°C)
R-type	0~1750°C	1°C/°F	±(0.2%+1°C)
S-type	0~1750°C	1°C/°F	±(0.2%+1°C)
N-type	-200~0°C	0.1°C/°F	±(0.2%+1°C)
	0~1300°C	0.1°C/°F	±(0.2%+0.5°C)
Feature			
Data hold	✓		
Data logging and Recall	1000 groups		
"°C/°F/k" selection	✓		
Backlight	✓		
Max/Min/Avg	✓		
USB interface	✓		
Channel	MS6513:Single ; MS6514: Dual		
General			
Power supply	4x1.5V AA batteries		
Weight	Approx. 510g		
Size	204mm x 93mm x 57mm		
Safety Rating	CE RoHS		

TEMPERATURE METERS



PM6508

Digital Humidity&Temperature Meter

ติดต่อบริษัท นีโอนิคส์ จำกัด
Tel: 02-077-7602 หรือ 061-8268939
E-mail: sale@neonics.co.th เว็บไซต์ www.neonics.biz

SPECIFICATIONS	Range	Resolution	Accuracy
Ambient temperature	-20°C ~ 0°C (-4°F ~ 32°F)	0.1°C/°F	±1.5°C
	0°C ~ 45°C (32°F ~ 113°F)	0.1°C/°F	±0.5°C
	45°C ~ 60°C (113°F ~ 140°F)	0.1°C/°F	±1.5°C
Relative Humidity	0% ~ 20%	0.1%	±4.0%
	20% ~ 80%	0.1%	±3.0%
	80% ~ 100%	0.1%	±4.0%
Wet Bulb Temperature	-20°C ~ 0°C (-4°F ~ 32°F)	0.1°C/°F	±1.5°C
	0°C ~ 45°C (32°F ~ 113°F)	0.1°C/°F	±0.5°C
	45°C ~ 60°C (113°F ~ 140°F)	0.1°C/°F	±1.5°C
Dew Point Temperature	-50°C ~ 0°C (-58°F ~ 32°F)	0.1°C/°F	±1.5°C
	0°C ~ 45°C (32°F ~ 113°F)	0.1°C/°F	±0.5°C
	45°C ~ 60°C (113°F ~ 140°F)	0.1°C/°F	±1.5°C
Feature			
Data hold	✓		
Data logging and Recall	100 groups		
"°C/°F" selection	✓		
Backlight	✓		
Max/Min	✓		
General			
Power supply	AAA1.5V x 4 Battery		
Weight	Approx. 190g		
Size	184mm×60mm×29mm		
Safety Rating	EN61010-1, EN61326-1		



HUMIDITY & TEMPERATURE METERS

