

Pressure Manometer



GM510



GM511

Technical indicators	GM510	GM511
Measuring range	±10kPa	
Precision	±0.3%FSO(25℃)	
Repeatability	±0.2%(Max+/-0.5 FSO)	
Linear/lag	±0.29 FSO	
Reaction time	0.5s	
Beyond the positive & negative pressure range	Err1&Err2	
Working temperature range	0~50℃	
Working humidity range	-10~60℃	
Peculiarity		
Large LCD backlit display	√	√
Temperature compensation	×	√
With differential mode & record mode	√	√
USB communication & data maintain	√	√
Zero and data correction function	√	√
Low electricity display	√	√
Auto power-off	√	√
Conventional		
Power supply	4*1.5V AAA batteries	

Pressure Manometer



GM520



GM505

Technical indicators	GM520	GM505
Measuring range	±35kPa	±2.49kPa
Precision	±0.3%FSO(25℃)	±0.25%FSO(25℃)
Repeatability	±0.2%(Max+/-0.5 FSO)	×
Linear/lag	±0.29 FSO	×
Reaction time	0.5s	
Beyond the positive & negative pressure range	Err1&Err2	
Working temperature range	0~50℃	
Working humidity range	-10~60℃	
Peculiarity		
Large LCD backlit display	√	√
Temperature compensation	×	√
With differential mode & record mode	√	√
USB communication & data maintain	√	√
Zero and data correction function	√	√
Low electricity display	√	√
Auto power-off	√	√
Conventional		
Power supply	4*1.5V AAA batteries	

LINE ID:@neonics



ติดต่อบริษัท เนโอเนิกส์ จำกัด

Tel: 02-077-7602 หรือ 061-8268939

E-mail: sale@neonics.co.th เว็บไซต์ www.neonics.biz