

DIGITAL SOUND LEVEL METER

MS6700 / MS6701

MS6700

SOUND LEVEL
30dB~130dB

FREQUENCY
31.5Hz~8KHz

dB Hz AUTO

Apo F/S A/C

MAX



MS6701

SOUND LEVEL
30dB~130dB

FREQUENCY
31.5Hz~8KHz

dB Hz MEM

AUTO Apo F/S

MAX A/C USB

RS 232C



Specifications MS6700 MS6701

Specifications	Range	Resolution	Accuracy
Sound Pressure	30dB~80dB	0.1dB	±1.5dB
	40dB~90dB	0.1dB	±1.5dB
	50dB~100dB	0.1dB	±1.5dB
	60dB~110dB	0.1dB	±1.5dB
	70dB~120dB	0.1dB	±1.5dB
	80dB~130dB	0.1dB	±1.5dB

Sample Rate		2 times/s	2 times/s
Dynamic	50dB		
Frequency	31.5Hz~8KHz		

Features

Display	counts	2000	2000
Data logging	records	16000	16000
Auto Ranging	Auto & Manual		
APO	Auto Power Off		
AC Signal Output	0.707 Vrms at FS (Auto-range mode isn't included) Output impedance approx. 600Ω		
DC Signal Output	10mV/dB Output impedance approx. 100Ω		
AC Adapter	Voltage 9VDC		
	Voltage Ripple < 100m Vpp		
	Supple Current > 100m ADC		
	Socket: pin Ground Casing Positive External Diameter 3.5mm		

Fast			
Slow			
A Weighting			
C Weighting			
Date and Time	Date and Time Display		
MAX			
Data Hold			
B.L	Display Backlight		
LBD	Low Battery Display		
Analog Bar	Analog Bar Indication		
UNDER / OVER	Over Range Indication		
RS-232 Pclink			
USB Interface			

General

Power Supply	6×1.5V AAA Batteries
Product Size	265mm×80mm×69mm/10.4"×3.15"×2.7"
Product Weight	317g/0.7lb
Safety Rating	CE(EMC) RoHS

● Feature Difference

ติดต่อบริษัท เนโอนิกส์ จำกัด

Tel: 02-077-7602 หรือ 061-8268939

E-mail: sale@neonics.co.th เว็บไซต์ www.neonics.biz

DIGITAL SOUND LEVEL METER

MS6702 / MS6708



MS6702

SOUND LEVEL
30dB~130dB

FREQUENCY
31.5Hz~8KHz

TEMPERATURE
-20°C~60°C

HUMIDITY
10~90% RH

dB Hz

AUTO Apo F/S

°F/°C MAX A/C

RS 232C



MS6708

SOUND LEVEL
30dB~130dB

FREQUENCY
31.5Hz~8KHz

dB Hz AUTO

Apo F/S MAX

A/C

RS 232C



Specifications MS6702 MS6708

Specifications	Range	Resolution	Accuracy
Sound Pressure	30dB~80dB	0.1dB	±1.5dB
	40dB~90dB	0.1dB	±1.5dB
	50dB~100dB	0.1dB	±1.5dB
	60dB~110dB	0.1dB	±1.5dB
	70dB~120dB	0.1dB	±1.5dB
	80dB~130dB	0.1dB	±1.5dB

Sample Rate		2 times/s	2 times/s
Dynamic	50dB		
Frequency	30Hz~8KHz		

Features

Display	counts	2000	2000
Data logging	records	16000	
Auto Ranging	Auto & Manual		
APO	Auto Power Off		
AC Signal Output	0.707 Vrms at FS (Auto-range mode isn't included) Output impedance approx. 600Ω		
DC Signal Output	10mV/dB Output impedance approx. 100Ω		
AC Adapter	Voltage 9VDC		
	Voltage Ripple < 100m Vpp		
	Supple Current > 100m ADC		
	Socket: pin Ground Casing Positive External Diameter 3.5mm		

Fast			
Slow			
A Weighting			
C Weighting			
Date and Time	Date and Time Display		
MAX			
Data Hold			
B.L	Display Backlight		
LBD	Low Battery Display		
Analog Bar	Analog Bar Indication		
UNDER / OVER	Over Range Indication		
RS-232 Pclink			
USB Interface			
°C/°F Selection			

General

Power Supply	1.5V AAA Battery	6	4
Product Size	265×80×69mm/10.4×3.15×2.7"		
Product Weight	317g/0.7lb		
Safety Rating	CE(EMC) RoHS		

● Feature Difference