

MOISTURE TESTER

MS6900 / MS6900A



MS6900

- DEPTH**
0~50mm
- RESOLUTION**
0.1%, 0.1°C, 0.1°F
0.1%RH
- °F/°C
- H₂O
- MAX MIN
- Backlight icon
- Battery icon



MS6900A

- DEPTH**
0~50mm
- RESOLUTION**
0.1%, 0.1°C, 0.1°F
0.1%RH
- °F/°C
- H₂O
- MAX MIN
- Backlight icon
- Battery icon



Specifications		MS6900
Specifications	Range	Accuracy
Depth		0~50mm
Ambient TEMP	-10°C~50°C/14°F~122°F	±0.2°C/±1°F
Electric Conductivity	0.0~60.0%	±1%
Humidity	10~90%	±5%
Features		
MAX/MIN		●
Sampling Rate	Moisture and Humiture	●
Unit Selection	%, WB, TD, °C, °F, %RH	●
Display Backlight		●
Data Hold		●
LBD	Low Battery Display	●
Materials Moisture Range		
1: (8.5~60%)	Beech, Spruce, Larch, Birch, Cherry, Walnut	
2: (6.8~53.4%)	Oak, Cedar, Maple, Ash Tree, Pink Shower Tree, Tamarisk	
3: (0.9~24.5%)	Smoothing Cement, Concrete	
4: (0.0~12.2%)	Anhydrite Screed	
5: (0.7~9.2%)	Cement Mortar	
6: (0.5~11.1%)	Lime Mortar, Plaster	
7: (0.0~17.8%)	Brick	
General		
Power Supply	2×1.5V AAA Batteries	
Product Size	130mm×56mm×29mm/5.1"×2.2"×1.1"	
Product Weight	120g/0.26lb	
Safety Rating	CE(EMC) RoHS	

Specifications		MS6900A
Specifications	Range	Accuracy
Depth		0~50mm
Ambient TEMP	-10°C~50°C/14°F~122°F	±0.2°C/±1°F
Electric Conductivity	0.0~60.0%	±1%
Humidity	10~90%	±5%
Features		
Auxiliary	Verification Test Points	●
MAX/MIN		●
Sampling Rate	Moisture and Humiture	●
Unit Selection	%, WB, TD, °C, °F, %RH	●
Display Backlight		●
Data Hold		●
LBD	Low Battery Display	●
Materials Moisture Range		
1: (8.5~60%)	Beech, Spruce, Larch, Birch, Cherry, Walnut	
2: (6.8~53.4%)	Oak, Cedar, Maple, Ash Tree, Pink Shower Tree, Tamarisk	
3: (0.9~24.5%)	Smoothing Cement, Concrete	
4: (0.0~12.2%)	Anhydrite Screed	
5: (0.7~9.2%)	Cement Mortar	
6: (0.5~11.1%)	Lime Mortar, Plaster	
7: (0.0~17.8%)	Brick	
General		
Power Supply	2×1.5V AAA Batteries	
Product Size	130mm×56mm×29mm/5.1"×2.2"×1.1"	
Product Weight	120g/0.26lb	
Safety Rating	CE(EMC) RoHS	

COMBUSTIBLE GAS DETECTOR

MS6310



MS6310

- RESOLUTION**
50 ppm
- ALARM**
10%~40%
- GAS
- LED

Specifications		MS6310
Specifications		
Resolution (methane)		50ppm
Alarm at Level		10%~40%
Warm Up Time		2 Minutes
Response time (40% LEL)		<2 Seconds
Feature		
Easy To Identify and Pinpoint Gas Leaks		●
Portable and High Sensitivity		●
Resume Original Measurement State after 7~10 minutes in Clean air		●
Gas Detected: Natural gas, Methane, Ethane, Propane, Butane, Acetone, Alcohol, Ammonia, Steam, Carbon Monoxide, Gasoline, Jet fuel, Hydrogen Solvents, Lacquer thinner, Naphtha		●
General		
Power Supply	4×1.5V AAA Batteries	
Product Size	172mm×70mm×46mm/6.8"×2.8"×1.8"	
Product Weight	354g/0.78lb	
Safety Rating	CE(EMC) RoHS	

