



Tube Rollers

Drawell tube rollers provide a gentle and highly efficient rolling motions, ideal for mixing blood samples, viscous substances and liquid-solid suspensions. Used in a variety of applications, such as the prevention of blood coagulation and immune precipitation, etc.

MX-T6-Pro

LCD Digital Tube Roller

Features:

- LCD displays the speed and time
- Speed range of 10~70rpm
- Six roller design for gentle rolling and easy to clean
- Continuous or timer operation

MX-T6-S

Tube Roller

Features:

- Speed range of 0~70rpm
- Six roller design for gentle rolling and easy to clean



LCD display







Specifications

Amplitude
Motor type
Rocking motion
Amplitude
Max. load capacity
Number of rollers
Roller size [length]
Speed range
Speed display
Timer
Timer display
Time setting range
Operation mode
Voltage
Power
Dimension [D×W×H]
Weight
Permissible ambient temperature and humidity
Protection class
FIOLECTION Class

MX-T6-Pro
24mm
DC motor
Rocking and rolling
24mm
4kg
6
280mm
10 ~70rpm
LCD
Yes
LCD
1~1199min
Continuous / timed
100~240V,50/60Hz
30W
450×260×120mm
5.1kg
5~40°C,80%
IP21

MX-T6-S
24mm
DC motor
Rocking and rolling
24mm
4kg
6
280mm
0~70rpm
Scale
-
-
-
Continuous
100~240V,50/60Hz
25W
450×260×120mm
4.5kg
5~40°C,80%
IP21

Line ID: @neonics



ติดต่อบริษัท นีโอนิคส์ จำกัด

Tel: 02-077-7602 หรือ 061-8268939

E-mail: sale@neonics.co.th เว็บไซต์ www.neonics.biz