

## Foam Hardness Tester/Memory Foam Hardness Tester



HT-6510F

Model: HT-6510F HT-6510MF

### Applications

- \* HT6510F is specially for sponge hardness measurement.
- \* HT-6510MF is used to measure memory foam hardness.
- \* Type F and Type MF are specially for determination of soft foam hardness, pillow hardness, and hardness of polyurethane foam rubber products.
- \* The large diameter presser foot and cylindrical indenter configuration allow measurement by direct application to the test specimen.



HT-6510MF

### Features

- \* It meets standards of DIN 53505, ISO 868, ISO 7619, ASTM D 2240, JISK7215.
- \* With average calculate, peak value hold function.
- \* Use RS-232 data output to connect with PC.
- \* Provide Bluetooth data output choice.
- \* The realization of hardness measurement of memory Foam.

### Specifications

Model	HT-6510F	HT-6510MF
Parameters	Tested Result/ Mean Value/ Max. Value	
Display Range	0~100HF	0~100HMF
Measurement Range	10~90HF	10~90HMF
Resolution	0.1HF	0.1HMF
Accuracy	$\leq \pm 1HF$	$\leq \pm 1HMF$
Spring Force	455gf	
Sensor Head Diameter	25mm	
Sensor Foot Diameter	80mm	
Battery Indicator	Low Battery Indicator	
Auto Switch Off	✓	

Model	HT-6510F	HT-6510MF
Operating Conditions	Temp.: 0~40 °C Humidity: 10~90 %RH	
Power Supply	4x1.5V AAA Size (UM-4) Battery	
Dimensions	162x80x80mm (6.4x3.1x3.1inch)	
Weight	490g	250g
Standard	Main Unit	
Accessories	Carrying Case(B04)	
	Operation Manual	
Optional	USB Data Cable with Software	
Accessories	Bluetooth Data Adapter with Software	

ติดต่อบริษัท เนโอนิคส์ จำกัด

Tel: 02-077-7602 หรือ 061-8268939

E-mail: sale@neonics.co.th เว็บไซต์ www.neonics.biz