

PRODUCT DATA SHEET

AMR302 2 IN 1 Brix & Refractive Index High Range



- ❑ Compact and Lightweight: In a small size, this digital brix refractometer is portable to take for measuring anywhere and anytime.
- ❑ High precision: AMTAST digital brix refractometer is of high precision. The measurement range is from 0.0-90.0% and refractive Index (RI) range is from 1.3330 to 1.5177nD.
- ❑ °C/°F switchable temperature display
- ❑ Automatic Temperature Control /Continuous loop read feature (15 times).

Feature:

- Measurement Units: Brix, Refractive Index
- Range: Brix: 0.0~90.0%, RI: 1.3330-1.5177nD
- Resolution: Brix/Salinity: 0.1%, RI : 0.0001nD
- Accuracy: Brix: $\pm 0.2\%$; RI: $\pm 0.0003\text{nD}$
- Temperature Compensation: ATC 10~60°C
- Auto Shut-Off: after 1 minutes
- Idle sample volume: 0.5ml
- Usage Environment: 10~40°C
- Power: 1.5V x 1 AAA Alkaline
- Size: 58 x 25 x 121mm
- Weight: 90g without battery.



ติดต่อบริษัท นีโอนิคส์ จำกัด

Tel: 098-479-5684 หรือ 061-8268939

E-mail: sale@neonics.co.th เว็บไซต์: www.neonics.biz