

# Hot Wire Anemometer GM8903/GT8911



Function	GM8903	GT8911
Wind speed/wind temperature/wind volume measurement	√	√
Wind speed/wind temperature/air volume unit conversion	√	√
Wind speed / wind volume maximum and minimum measurement	√	√
Air volume 2/3, max value, average value measurement	√	√
Data retention, storage, and deletion functions	√	√
Low battery indicator function	√	√
Automatic shutdown	√	√
Backlight function	√	√
USB connection function	√	√
Button sound prompt	√	√
Large screen LCD display	√	√
Rechargeable function	×	√

## Application



School



Factory



Office



Traffic highway

## Specification

### ▶ Wind Velocity Range:

	GM8903	GT8911
m/s	0.0-30.0	0.0-30.0
Ft/min	0.0-5860	0.0-5904
Knots	0.0-55.0	0.0-58.3
Km/h	0.0-90.0	0.0-108.0
Mph	0.0-65	0.0-67

### ▶ Air Temperature Range: 0.0-45.0°C (32.0-113.0°F)

### ▶ Power supply

	GM8903	GT8911
Power supply	AAA 1.5V Alkaline battery *4	3.7V lithium-ion batteries

### ▶ Dimensions

	GM8903	GT8911
Dimensions	77x36x164mm	73x38x194mm

### ▶ Wind flow range:

CMM: 0-999900m<sup>3</sup> /min  
CFM: 0-999900 ft<sup>3</sup> /min



USB cable  
(GM8903)



Screw holes



Connector



Charging port



USB cable  
(GT8911)

ติดต่อบริษัท เน็ โอนิกส์จำกัด

Tel: 098-479-5684 หรือ 061-8268939

E-mail: sale@neonics.co.th เว็บไซต์ www.neonics.biz