GT770 Portable pH Meter



Feature:

- Automatic/manual data recording, report generation
- Data storage, viewing, deletion
- Adjustable sampling time interval
- Adjustable automatic shutdown time
- Self-calibration, optional [4.00]-[6.86]-[9.18] or [4.00]-[7.00]-[10.00]
- Temperature unit selection
- Restore factory settings
- Adjustable screen brightness
- Low battery prompt and power prompt
- USB charging Connect to PC software to transfer data

Specifications:

- pH range: 0.00~14.00
- pH resolution: 0.01
- pH accuracy: ±0.05
- Temperature range: 0~60℃ (32~140℉)
- Temperature resolution: 0.1℃
- Temperature accuracy: ±1.0℃
- Voltage range : -500~500mV
- Voltage resolution: 1mV
- Voltage accuracy: ±3%
- Temperature compensation range: 0~60℃ (32~140℉)
- Working environment: 0~50℃ (32~122℉), ≤85%RH
- Storage space: 8MB (can store about 397,000 data)
- Battery: lithium battery 3.7V 1000mAh
- Low battery warning: 4 levels of battery indication, automatically shut down when lower than 3.3V
- Charging adapter: 5V/2A
- Product size: 160*65.35*35mm

ติดต่อ บริษัท นีโอนิคส์ จำกัด

333/81 ถนนเลียบวารี แขวงโคกแฝด เขตหนองจอก กรุงเทพฯ 10530

Tel: 061-8268939, 098-4795684 E-mail: sale@tools.in.th และ sale@neonics.co.th